Data sheet
826 PUZ-G082

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors z radu 826 PUZ includes montážnu dosku na four otvory, which ensures stable mounting. Wheel centre is made z impact-resistant design polyamidu with antikoróznou finish v bielej farbe, which resists wear. Tread z thermoplastic polyurethane elastomer is non-detachably mechanicky combined with wheel centre, which guarantees excellent elasticity and schopnosť absorbovať high load, while jeho non-marking operation nepoškodzuje floor and is suitable for straight polyurethane surfaces. Thanks to pozinkovanej vidlici z steel plechu thickness 6 až 7 mm and kalenému ball bearing with dvomi radiálnymi ložiskami and krytmi achieves high durability against corrosion and hladkú, bezúdržbovú rotáciu. An ideal choice for nízkozdvižné and vysokozdvižné ručné trolleys, where important reliability and gentleness k podlahám.

Bracket 826 series:

Swivel castor with top plate (4 bolt holes)

- heavy-duty version
- pressed steel, THK 6 ÷ 7 mm
- shaped and hardened bearing
- zinc-plated, Cr6-free

Wheel PUZ series:

Wheel center:

- impact-resistant structural polyamide
- corrosion-resistant
- white color

Tread:

- thermoplastic polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity and absorption of high load capacity
- notch toughness
- very good floor preservation
- non-marking
- brown color

Application:

- flat polyurethane floors
- primarily intended for pallet trucks and forklift trucks

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).

Specifications

Diameter (D)	82 mm
Wheel width (S)	60 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	54 mm
Mounting height(H)	125 mm
Load	510 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Čierna
Wheel centre colour	Black
Wheel centre	Polyamide