Data sheet
422FX CFZ-K100

Nerezové otočné rolovacie koliesko s brzdou - spôsob upnutia: montážna doska na štyri otvory (príruba).



VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

INOX
NEHRDZAVEJÚCA OCEĽ

The design of this wheel spočíva v spoľahlivom spojení thermoplastic elastomérového tread with durable wheel centre, which ensures long service life aj during intenzívnej operation. Klzné bearing allows non-marking operation and minimises potrebu maintenance, thereby reduces operating náklady. An ideal choice for use v industrial and komerčných priestoroch, where important durability and gentleness k podlahovým krytinám. Zinc-plated vidlica dodáva dodatočnú protection against corrosion, which increases durability v demanding conditions.

TREAD AND TYRE HARDNESS	85° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -25 °C do +250 °C	

Specifications

Diameter (D)		100 mm
Plate size (A x B)		105 x 80 mm
Bolt hole spacing (a x b)		80 x 60 mm
Bolt holes Ø		9 mm
Offset (F)		40 mm
Mounting height(H)		128 mm
Load		125 kg
Bearing type		Klzné
Mounting type		Mounting bracket
Tread material		Plastic
Attributes		Nehrdzavejúce prevedenie
Wheel centre colour		Black
Wheel centre		Polyamide
Typ brzdy		F
Wheel width (S)		35 mm

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).