Data sheet
636 XJ-G260

Fixed castor - mounting type: top plate (4 bolt holes).



The design tejto kolesovej series spočíva v spojení durable polypropylene wheel centre with rubber tread z thermoplastic elastomer, which ensures low hlučnosť and gentleness k povrchom. Thanks to the use of klzného bearing ensures maintenance-free operation with dlhou service lifeou, while the zinc-plated vidlica increases durability against corrosion. Toto wheel is optimalizované for indoor use v environments such as sklady, kancelárie alebo industrial haly, where important quiet operation and ochrana floors.

TREAD AND TYRE HARDNESS	60° Shore A	●○○○○
ROLLING RESISTANCE	good	●●●○○
OPERATING NOISE	excellent	●●●●●
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	od -20 °C do +50 °C	

Specifications

Diameter (D)		260 mm
Wheel width (S)		85 mm
Bearing type		Ball
Plate size (A x B)		115x100 mm
Bolt hole spacing (a x b)		85x72 mm
Bolt holes Ø		11 mm
Mounting height(H)		320 mm
Load		80 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).