Data sheet
634 PUC-K160 AS

Fixed castor - mounting type: top plate (4 bolt holes).





VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

ESD

The design of this castor uses fixed montážnu dosku na four otvory, which allows spoľahlivé mounting v demanding conditions. Wheel centre is made z durable material, while the tread z thermoplastic elastomer ensures quiet and gentle movement na various povrchoch. Klzné bearing ensures smooth and maintenance-free chod, thereby reduces opotrebovanie and increases service life. Toto castor is suitable for use v industrial environments, where dôraz na durability and reliability, while jeho dizajn podporuje efektívnu manipuláciu with nákladmi.

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)	160 mm
Wheel width (S)	40 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	200 mm
Load	500 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	
Farba behúňa	Sivá
Wheel centre colour	Black
Wheel centre	Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).