Data sheet
724T LU-G150-50-50 BR

Swivel castor - mounting type: top plate (4 bolt holes).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)		150 mm
Plate size (A x B)		135 × 110 mm
Bolt hole spacing (a x b)		105 × 80/75 mm
Bolt holes Ø		11 mm
Offset (F)		56 mm
Mounting height(H)		200 mm
Load		700 kg
Bearing type		guličkové
Typ brzdy		T
Mounting type		Mounting bracket
Attributes		
Farba behúňa		Hnedá
Wheel centre colour		Hliníková
Wheel centre		Šedá liatina

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).