Data sheet
624F ALE-G160

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors uses hliníkovú liatinu for wheel centre so reinforced uzatvoreným rebrovaním, which increases durability and antikoróznu protection. Tread z plnej elastickej rubber is navulkanizovaný na wheel centre, which ensures nerozoberateľné spojenie with vynikajúcou priechodnosťou cez nerovnosti and výborným tlmením vibrácií. Thanks to dvom radiálnym ball ložiskám with krytmi and tesneniu otočenia achieves maintenance-free operation and long service life. Mechanizmus brake F allows zablokovanie rotation wheel and vidlice v current direction, which increases safety during statickom umiestnení. Model is určený for tvrdé floor, such as are pancierové, ale vďaka odolnému prevedeniu is suitable aj na nerovné surfaces, while mounting doska na four otvory uľahčuje installation.

Bracket 624 series:

Swivel castor with top plate (4 bolt holes)

- medium-duty version
- pressed steel, THK 4 ÷ 5 mm
- double ball bearing with calibrated races
- swivel head seal
- zinc-plated, Cr6-free

Discription of the brake F:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel ALE series:

Wheel center:

- aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

Tread:

- elastic solid rubber
- chemically-bonded inseparable connection with the wheel center (vulkanized)
- excellent at crossing obstacles
- vibration-absorbing
- silent operation

TREAD AND TYRE HARDNESS	65° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	good	●●●○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -30 °C do +80 °C	

Specifications

Diameter (D)	160 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 × 110 mm
Bolt hole spacing (a x b)	105 × 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	200 mm
Load	350 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Guma a TPE
Attributes	Nízka hlučnosť
Farba behúňa	Čierna
Wheel centre colour	Hliníková
Wheel centre	Hliníková liatina
Typ brzdy	F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).