Data sheet
623T PUO-G150

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors with brake uses vidlicu series 623 with pozinkovaným povrchom without Cr6, which ensures antikoróznu protection and long service life v demanding environments. Wheel centre z impact-resistant design polyamidu so reinforced load-bearing rebrom and antikoróznou čiernou farbou is non-detachably mechanicky combined with behúňom z thermoplastic polyurethane elastomer, which provides excellent elasticity and absorpciu vysokých záťaží, while krémová bezstopá farba saves floor. Dvojité axial bearing with kalibrovanými dráhami and tesnením otočia ensures plynulý and maintenance-free chod, while the mechanizmus brake T blocks rotation wheel and vidlice v current direction for bezpečnú stabilizáciu. An ideal choice for ručné transport equipment, where potrebná durability, quiet operation and jednoduchá montáž cez four otvory na prírube.

Bracket 623 series:

Swivel castor with top plate (4 bolt holes)

- standard version
- pressed steel, THK 3 ÷ 4 mm
- double bearing with calibrated races
- seal in the swivel head
- zinc-plated, Cr6-free

Discription of the brake T:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel PUO series:

Wheel center:

- impact-resistant structural polyamide
- reinforced bearing rib
- corrosion-resistant
- black color

Tread:

- thermoplastic polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity and absorption of high load capacity
- notch toughness

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)	150 mm
Wheel width (S)	45 mm
Plate size (A x B)	135 × 110 mm
Bolt hole spacing (a x b)	105 × 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	195 mm
Load	350 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Krémová
Wheel centre colour	Black
Wheel centre	Polyamide
Typ brzdy	T

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).