Data sheet
623F PUC-K200 BR

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors includes vidlicu z pozinkovanej steel without Cr6, which provides antikoróznu protection and dvojité axial bearing with kalibrovanými dráhami for smooth movement. Wheel centre z impact-resistant polyamidu so reinforced load-bearing rebrom and antikoróznou finish is non-detachably mechanicky combined with behúňom z thermoplastic polyurethane elastomer, which guarantees excellent elasticity and schopnosť absorbovať high load. Thanks to klznému bearing, which is bezúdržbové and odolné to dirt and external vplyvom, is toto castor suitable for ručné transport equipment na short až dlhšie transport distances. Mechanizmus brake F locks rotation wheel and vidlice v current direction, thereby increases safety and stability during handling.

Bracket 623 series:

Swivel castor with top plate (4 bolt holes)

- standard version
- pressed steel, THK 3 ÷ 4 mm
- double bearing with calibrated races
- seal in the swivel head
- zinc-plated, Cr6-free

Discription of the brake F:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel PUC series:
Wheel center:

- impact-resistant structural polyamide
- reinforced bearing rib
- corrosion-resistant
- color natural white

Tread:

- thermoplastic polyurethane elastomer
- chemically-bonded inseparable connection with the wheel cente
- good elasticity and absorption of high load capacity
- notch toughness
- very good floor preservation
- non-marking

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)	200 mm
Wheel width (S)	40 mm
Plate size (A x B)	135 × 110 mm
Bolt hole spacing (a x b)	105 × 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	240 mm
Load	350 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Hnedá
Wheel centre colour	Prírodná biela
Wheel centre	Polyamide
Typ brzdy	F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).