Data sheet
734 PUC-G160 BR

Fixed castor - mounting type: top plate (4 bolt holes).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design series 734 uses fixed rolovaciu konštrukciu with mounting doskou na four otvory, which allows simple and bezpečnú installation. Vidlica is made z pozinkovaného steel plechu without Cr6, which increases durability against corrosion and predlžuje service life. Tvarovo zosilnený steel plech provides zvýšenú strength and stability during zaťažení. Thanks to the use of kvalitných ložísk ensures castor plynulý and quiet operation, ideálne for industrial applications, where important reliability and minimálna maintenance. An ideal choice for vybavenie trolleys, racks and iných industrial equipment v demanding conditions.

Bracket 734 series:

Fixed castor with plug-in solid stem

- shaped and hardened bearing
- zinc-plated, Cr6-free

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)		160 mm
Wheel width (S)		40 mm
Plate size (A x B)		135 x 110 mm
Bolt hole spacing (a x b)		105 x 80/75 mm
Bolt holes Ø		11 mm
Mounting height(H)		205 mm
Load		500 kg
Bearing type		Ball
Mounting type		Mounting bracket
Tread material		Polyuretán
Attributes		Non-marking
Farba behúňa		Hnedá
Wheel centre colour		Prírodná biela
Wheel centre		Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).