Data sheet
825 PUC-G160 BR

Swivel castor - mounting type: top plate (4 bolt holes).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this castor uses wheel centre z impact-resistant polyamidu with antikoróznym povrchom and osilneným rebrom, which increases jeho load capacity and trvanlivosť. Tread z thermoplastic polyurethane elastomer is mechanicky combined with wheel centre, which guarantees excellent elasticity and schopnosť absorbovať high load without poškodenia floors. An ideal choice for short aj dlhé transport vzdialenosti, where ball bearing with dvoma radiálnymi radmi and krytmi ensures smooth and maintenance-free movement, while the zinc-plated vidlica without Cr6 increases resistance to corrosion v demanding environments.

Bracket 825 series:

Swivel castor with top plate (4 bolt holes)

- heavy-duty version
- pressed steel, THK 5 ÷ 7 mm
- shaped and hardened bearing
- zinc-plated, Cr6-free

Wheel PUC series:

Wheel center:

- impact-resistant structural polyamide
- reinforced bearing rib
- corrosion-resistant
- color natural white

Tread:

- thermoplastic polyurethane elastomer
- chemically-bonded inseparable connection with the wheel cente
- good elasticity and absorption of high load capacity
- notch toughness
- very good floor preservation
- non-marking
- brown color

Application:

- manual handling equipment
- short transport distances (PUC-K)
- long transport distances(PUC-G)

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)	160 mm
Wheel width (S)	40 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	50 mm
Mounting height(H)	205 mm
Load	500 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Hnedá
Wheel centre colour	Prírodná biela
Wheel centre	Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).