Data sheet
828 ALSE-G252 D1

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model 828 ALSE D1 predstavuje swivel rolovacie castor with mounting doskou na four otvory, which allows stable mounting cez prírubu. Thanks to the use of high-quality thermoplastic elastomer v behúni and pozinkovanej vidlice achieves high resistance to wear and corrosion. Technické parametre zahŕňajú plain bearing, which ensures maintenance-free operation and smooth movement without potreby mazania. An ideal choice for applications v industrial alebo komerčných priestoroch, where important quiet operation and gentleness k surface floor. Konštrukcia castors podporuje bezstopý movement and long service life aj during intenzívnom zaťažení.

TREAD AND TYRE HARDNESS	65° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	good	●●●○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -30 °C do +80 °C	

Specifications

Diameter (D)	252 mm
Wheel width (S)	76 mm
Plate size (A x B)	195 x 160 mm
Bolt hole spacing (a x b)	160 x 120 mm
Bolt holes Ø	14,5 mm
Offset (F)	72 mm
Mounting height(H)	310 mm
Load	600 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Guma a TPE
Attributes	Nízka hlučnosť
Farba behúňa	Čierna
Wheel centre colour	Hliníková
Wheel centre	Hliníková liatina

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).