Data sheet
623 ALE-G200

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors includes vidlicu series 623 vyrobenú z steel plechu thickness 3 až 4 mm with pozinkovaním without Cr6, which increases durability against corrosion. Wheel centre is made z hliníkovej liatiny so reinforced uzatvoreným rebrovaním and antikoróznym hliníkovým náterom, which ensures strength and long service life. Tread z plnej elastickej rubber is navulkanizovaný na wheel centre, which zabraňuje rozoberaniu and zlepšuje priechodnosť cez nerovnosti. Dvojité axial bearing with kalibrovanými dráhami and tesnením otočenia, doplnené dvomi radiálnymi guličkovými ložiskami with krytmi, ensures maintenance-free operation and smooth movement. An ideal choice for use na tvrdých pancierových floors and nerovných povrchoch, where provides high durability and quiet operation.

Bracket 623 series:

Swivel castor with top plate (4 bolt holes)

- standard version
- pressed steel, THK 3 ÷ 4 mm
- double bearing with calibrated races
- seal in the swivel head
- zinc-plated, Cr6-free

Wheel ALE series:

Wheel center:

- aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

Tread:

- elastic solid rubber
- chemically-bonded inseparable connection with the wheel center (vulkanized)
- excellent at crossing obstacles
- vibration-absorbing
- silent operation
- black color

TREAD AND TYRE HARDNESS	65° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	good	●●●○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -30 °C do +80 °C	

Specifications

Diameter (D)		200 mm
Wheel width (S)		50 mm
Plate size (A x B)		135 × 110 mm
Bolt hole spacing (a x b)		105 × 80/75 mm
Bolt holes Ø		11 mm
Offset (F)		56 mm
Mounting height(H)		240 mm
Load		350 kg
Bearing type		Ball
Mounting type		Mounting bracket
Tread material		Guma a TPE
Attributes		Nízka hlučnosť
Farba behúňa		Čierna
Wheel centre colour		Hliníková
Wheel centre		Hliníková liatina

Application:

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).