Data sheet
623T PUC-K200 AS

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

ESD

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

The design of this castor includes vidlicu zo zinkovanej oceľovej dosky with dvojitým axial bearing and tesnením otoča, which zlepšuje resistance to dirt and external vplyvom. Thanks to the use of klzného bearing is bezúdržbové and suitable na short transport distances. Tread z thermoplastic polyurethane elastomer is non-detachably mechanicky combined with wheel centre, which provides excellent elasticity and schopnosť absorbovať high load. Brzdový mechanizmus typu T allows zablokovanie rotation wheel and vidlice v current natočení, thereby increases safety during handling. An ideal choice for ručné transport equipment v environments vyžadujúcich antistatické vlastnosti and gentleness k podlahám.

Bracket 623 series:

Swivel castor with top plate (4 bolt holes)

- standard version
- pressed steel, THK 3 ÷ 4 mm
- double bearing with calibrated races
- seal in the swivel head
- zinc-plated, Cr6-free

Discription of the brake T:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel PUC AS series:

Wheel center - antistatic:

- impact-resistant structural polyamide
- reinforced bearing rib
- corrosion-resistant
- antistatic $10^5 \leq R \leq 10^7$ Ω
- black color

Tread - antistatic:

- thermoplastic polyurethane elastomer
- chemically-bonded inseparable connection with the wheel cente
- good elasticity and absorption of high load capacity
- notch toughness
- very good floor preservation
- non-marking

Specifications

Diameter (D)	200 mm
Wheel width (S)	40 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	240 mm
Load	350 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	
Farba behúňa	Sivá
Wheel centre colour	Black
Wheel centre	Polyamide
Typ brzdy	T

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).