Data sheet
623AN2 CPC-G160





The design of this samostatného wheel uses durable polypropylénový wheel centre combined with rubber tread z thermoplastic elastomer, which minimises noise and protects surfaces. Klzné bearing ensures non-marking operation and eliminuje potrebu mazania, thereby zjednodušuje údržbu. Zinc-plated vidlica increases resistance to corrosion, which is advantageous v various environments. An ideal choice for applications vyžadujúce reliable and quiet movement, such as are skladové alebo industrial trolleys.

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).