Data sheet
724TAk ALUO-G150 zadný výrez

Swivel castor - mounting type: top plate (4 bolt holes).

The design of this castor includes zinc-plated vidlicu and ihličkové bearing, which guarantees a long service life and maintenance-free operation v demanding environments. Thanks to the use of thermoplastic elastomer v behúni achieves quiet operation and resistance to wear, while mounting doska na four otvory allows simple and bezpečnú installation. An ideal choice for applications vyžadujúce precise manoeuvring and stability, such as are industrial trolleys alebo furniture v komerčných priestoroch.

TREAD AND TYRE HARDNESS	87° ± 5° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).