Data sheet
724 PUC-K200 AS

Swivel castor - mounting type: top plate (4 bolt holes).





VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

ESD

The design of this swivel rolovacieho castors includes vidlicu series 724 with mounting doskou na four otvory, vyrobenú z steel plechu thickness 4 až 6 mm and zinc-plated without Cr6, which increases antikoróznu durability. Wheel centre is made z antistatického impact-resistant polyamidu so reinforced load-bearing rebrom, farbou čierna, while the tread pozostáva z antistatického thermoplastic polyurethane elastomer, farby sivá, which is non-detachably mechanicky combined with wheel centre, which ensures excellent elasticity, absorbciu vysokej záťaže and vrubovú húževnatosť. Use klzného bearing, tvoreného material wheel centre, allows maintenance-free operation, high resistance to dirt, external vplyvom and zmenám prostredia, vhodnú for short transport distances. Thanks to antistatickým vlastnostiam and bezstopému chodu is an ideal choice for ručné transport equipment, where vyžaduje gentleness k podlahám and reliability v demanding conditions.

Bracket 724 series:

Swivel castor with top plate (4 bolt holes)

- heavy-duty version
- pressed steel, THK 4 ÷ 6 mm
- shaped and hardened bearing
- zinc-plated, Cr6-free

Wheel PUC AS series:

Wheel center - antistatic:

- impact-resistant structural polyamide
- reinforced bearing rib
- corrosion-resistant
- antistatic $10^5 \leq R \leq 10^7$ Ω
- black color

Tread - antistatic:

- thermoplastic polyurethane elastomer
- chemically-bonded inseparable connection with the wheel cente
- good elasticity and absorption of high load capacity
- notch toughness
- very good floor preservation
- non-marking
- antistatic $10^5 \leq R \leq 10^7$ Ω
- gray color

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)	200 mm
Wheel width (S)	40 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	245 mm
Load	600 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	
Farba behúňa	Sivá
Wheel centre colour	Black
Wheel centre	Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).