Data sheet
724F PUC-G200 AS

Swivel castor - mounting type: top plate (4 bolt holes).

VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

ESD

The series model 724 predstavuje swivel rolovacie castor with brake, which is konštruované for vysoko odolné use. The design includes zinc-plated vidlicu z steel plechu with hrúbkou 4-6 mm and kovaný nosný diel bearing. Thanks to the use of antistatického polyamide wheel centre so reinforced load-bearing rebrom and thermoplastic polyurethane elastomer v behúni achieves excellent elasticity and durability against nárazom. Ball bearing ensures plynulý and maintenance-free chod, while the brzdový mechanizmus allows zablokovanie rotation wheel and vidlice. An ideal choice for applications vyžadujúce antistatické vlastnosti and gentleness k podlahám.

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Bracket 724 series:

Swivel castor with top plate (4 bolt holes)

- heavy-duty version
- pressed steel, THK 4 ÷ 6 mm
- shaped and hardened bearing
- zinc-plated, Cr6-free

Discription of the brake F:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel PUC AS series:

Wheel center - antistatic:

- impact-resistant structural polyamide
- reinforced bearing rib
- corrosion-resistant
- antistatic $10^5 \leq R \leq 10^7$ Ω
- black color

Tread - antistatic:

- thermoplastic polyurethane elastomer
- chemically-bonded inseparable connection with the wheel cente
- good elasticity and absorption of high load capacity
- notch toughness
- very good floor preservation
- non-marking
- antistatic $10^5 \leq R \leq 10^7$ Ω
- gray color

Specifications

Diameter (D)	200 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	245 mm
Load	600 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	
Farba behúňa	Sivá
Wheel centre colour	Black
Wheel centre	Polyamide
Typ brzdy	F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity = 40%-70%).