Data sheet
734 PUC-K200 AS

Fixed castor - mounting type: top plate (4 bolt holes).

VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

ESD

The design of this pevného rolovacieho castors uses vidlicu zo zinkovaného steel plechu so zvýšenou pevnosťou, which allows montáž na four otvory. Wheel centre z antistatického impact-resistant polyamidu so reinforced load-bearing rebrom provides excellent durability and antikoróznu protection. Tread z thermoplastic polyurethane elastomer is non-detachably mechanicky combined with wheel centre, which ensures excellent elasticity and schopnosť absorbovať high load. Thanks to klznému bearing, which is tvorené material wheel centre, ide a bezúdržbové riešenie odolné to dirt and external vplyvom. An ideal choice for ručné transport equipment na short transport distances, where important reliability and gentleness k podlahám.

Bracket 734 series:

Fixed castor with plug-in solid stem

- shaped and hardened bearing
- zinc-plated, Cr6-free

Wheel PUC AS series:

Wheel center - antistatic:

- impact-resistant structural polyamide
- reinforced bearing rib
- corrosion-resistant
- antistatic $10^5 \leq R \leq 10^7$ Ω
- black color

Tread - antistatic:

- thermoplastic polyurethane elastomer
- chemically-bonded inseparable connection with the wheel cente
- good elasticity and absorption of high load capacity
- notch toughness
- very good floor preservation
- non-marking
- antistatic $10^5 \leq R \leq 10^7$ Ω
- gray color

Application:

- manual handling equipment

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)	200 mm
Wheel width (S)	40 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	245 mm
Load	600 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	
Farba behúňa	Sivá
Wheel centre colour	Black
Wheel centre	Polyamide

Bearing - plain bore:

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).