Data sheet
724F ZU-G125

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors with brake uses zinc-plated vidlicu with mounting doskou na four otvory, which is vysoko durable and suitable for steel plechy thickness 4 až 6 mm. Thanks to the use of dvoch radiálnych guličkových ložísk with krytmi ensures smooth and maintenance-free chod, while mechanizmus brake locks rotation wheel and vidlice v current direction. Wheel centre is made z vysoko odolnej zváranej oceľovej konštrukcie with lakovaným sivým povrchom, while the tread z liateho polyurethane elastomer is non-detachably chemicky combined with wheel centre, which guarantees excellent elasticity and schopnosť absorbovať high load. An ideal choice for tvrdé aj mäkké industrial floor with miernymi nerovnosťami, keďže nepoškodzuje and nefarbí surfaces, offers nízky rozbehový and valivý odpor and is suitable for nepretržitú operation.

Bracket 724 series:

Swivel castor with top plate (4 bolt holes)

- heavy-duty version
- pressed steel, THK 4 ÷ 6 mm
- shaped and hardened bearing
- zinc-plated, Cr6-free

Discription of the brake F:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel ZU series:

Wheel center:

- highly durable welded steel construction made of forged sheets
- lacquered
- grey color

Tread:

- casted polyurethane elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity, good at preserving floor surfaces
- notch toughness
- non-marking
- low level of starting and rolling resistance
- brown color

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)		125 mm
Wheel width (S)		50 mm
Plate size (A x B)		135 x 110 mm
Bolt hole spacing (a x b)		105 x 80/75 mm
Bolt holes Ø		11 mm
Offset (F)		56 mm
Mounting height(H)		170 mm
Load		500 kg
Bearing type		Ball
Mounting type		Mounting bracket
Tread material		Polyuretán
Attributes		Non-marking
Farba behúňa		Žlto-Hnedá
Wheel centre colour		Sivá
Wheel centre		Oceľ
Typ brzdy		F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).