Data sheet
633P CPC-K200

Fixed castor - mounting type: top plate (4 bolt holes), with brake.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this pevného rolovacieho castors includes montážnu dosku na four otvory, which allows simple and stable installation. Zinc-plated vidlica z steel plechu increases durability against corrosion, while the vstrekovaný polyamide wheel centre provides excellent chemickú resistance to alkoholu, soliam, tukom and zriedeným kyselinám či zásadám. Klzné bearing ensures maintenance-free operation with odolnosťou to dirt and external vplyvom, thereby minimises potrebu maintenance. Mechanizmus brake with dvojpákovým prevedením ON/OFF allows quick and spoľahlivé zablokovanie rotation wheel for bezpečnú manipuláciu. Thanks to týmto vlastnostiam is castor suitable for use na rovných, polyuretánových floors, equipment with trvalou záťažou and krátkych prepravných vzdialenostiach, where combines durability and practical funkčnosť.

Bracket 633 series:

Fixed castor with top plate (4 bolt holes)

- pressed steel
- zinc-plated, Cr6-free

Discription of the brake P:

- the brake system prevents the rotation of the wheel double-lever ON/OFF version

Wheel CPC series:

Injection polyamide:

- corrosion-free
- high chemical resistance to alcohol, salts, fats, some acids and bases in dilute concenrations (see spreadsheet chemical resistance of materials)
- natural white color

Application:

- even polyurethane floors
- equipment with a permanent load
- short distances (CPB-K)
- long distances (CPB-g)

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

Diameter (D)	200 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	240 mm
Load	350 kg
Bearing type	Klzné
Typ aretácie	-
Mounting type	Mounting bracket
Tread material	Plastic
Attributes	Non-marking
Wheel centre colour	Prírodná biela
Wheel centre	Polyamide
Typ brzdy	P

Bearing - plain bore:

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).