Data sheet
734P CPC-K200

Fixed castor - mounting type: top plate (4 bolt holes), with brake.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model 734P CPC predstavuje fixed rolovacie castor with mounting doskou na four otvory and integrovanou brake. Thanks to the use of tvarovo zosilneného steel plechu with pozinkovaním without Cr6 achieves zvýšenú strength and resistance to corrosion. Polyamidový wheel centre with klzným bearing ensures maintenance-free chod durable to dirt and external vplyvom, while is suitable na short transport distances. Mechanizmus brake with dvojpákovým prevedením ON/OFF allows jednoduché zablokovanie rotation wheel. An ideal choice for straight polyurethane floor and applications vyžadujúce high chemickú resistance to alkoholu, soliam, tukom and zriedeným kyselinám či zásadám.

Bracket 734 series:

Fixed castor with plug-in solid stem

- shaped and hardened bearing
- zinc-plated, Cr6-free

Discription of the brake P:

- the brake system prevents the rotation of the wheel double-lever ON/OFF version

Wheel CPC series:

Injection polyamide:

- corrosion-free
- high chemical resistance to alcohol, salts, fats, some acids and bases in dilute concenrations (see spreadsheet chemical resistance of materials)
- natural white color

Application:

- even polyurethane floors
- equipment with a permanent load
- short distances (CPB-K)
- long distances (CPB-g)

Bearing - plain bore:

- formed by wheel center material

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

Diameter (D)	200 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	245 mm
Load	700 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Plastic
Attributes	Non-marking
Wheel centre colour	Prírodná biela
Wheel centre	Polyamide
Typ brzdy	P

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity = 40%-70%).