Data sheet
734P CPC-G150

Fixed castor - mounting type: top plate (4 bolt holes), with brake.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this pevného rolovacieho castors includes zinc-plated vidlicu z tvarovo zosilneného steel plechu, which increases strength and resistance to corrosion without použitia Cr6. Wheel z vstrekovaného polyamidu, séria CPC, is vysoko odolné to chemicals such as alkohol, soli, tuky and zriedené kyseliny či zásady, suitable for equipment with trvalou záťažou. Dvojpáková brake P mechanizmus allows jednoduché blokovanie rotation wheel v režime ON/OFF, zabezpečujúc bezpečnú manipuláciu. Use dvoch radiálnych guličkových ložísk with krytmi guarantees plynulý and maintenance-free chod, ideálny for dlhé transport distances na rovných, polyuretánových floors, thereby minimises opotrebovanie and increases service life.

Bracket 734 series:

Fixed castor with plug-in solid stem

- shaped and hardened bearing
- zinc-plated, Cr6-free

Discription of the brake P:

- the brake system prevents the rotation of the wheel double-lever ON/OFF version

Wheel CPC series:

Injection polyamide:

- corrosion-free
- high chemical resistance to alcohol, salts, fats, some acids and bases in dilute concenrations (see spreadsheet chemical resistance of materials)
- natural white color

Application:

- even polyurethane floors
- equipment with a permanent load
- short distances (CPB-K)
- long distances (CPB-g)

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

Diameter (D)	150 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	200 mm
Load	700 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Plastic
Attributes	Non-marking
Wheel centre colour	Prírodná biela
Wheel centre	Polyamide
Typ brzdy	P

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).