Data sheet
623X CZC-K160

Nerezové otočné rolovacie koliesko - spôsob upnutia: montážna doska na štyri otvory (príruba).



VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

INOX
NEHRDZAVEJÚCA OCEĽ

Vidlica series 623X is made z nerezového plechu and disponuje dvojitým axial bearing with nerezovými guličkami, which guarantees a long service life and smooth chod. Wheel series CZC má vstrekovaný teplotne durable polyamide wheel centre, which is durable to vysokým temperatures and prasknutiu, with prírodnou bielou farbou. Thanks to the use of klzného bearing, tvoreného material wheel centre, ensures maintenance-free operation and resistance to dirt and external vplyvom. An ideal choice for lakovne, where krátkodobo resists teplote do +240°C, while teplota wheel nesmie prekročiť +150°C, which platí len during použití montážneho kompletu with teflónovým povrchom. Suitable na short transport distances.

Bracket 623X series:

Swivel castor for with top plate (4 bolt holes)

- stainless steel
- double axial bearing with stainless steel balls

Wheel CZC series:
Injection heat-resistant polyamide:

- abrasion resistant
- natural white color

Application:

- paint shops
- oven temperature short-term up to +240°C
- wheel temperature must not exceed +150 °C

*temperature resistance only applies when using a teflon tube

Bearing - plain bore:

- formed by wheel center material
- maintenance-free
- resistant to dirt and external influences and environmental changes
- suitable for short distances

TREAD AND TYRE HARDNESS	85° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -25 °C do +150 °C	

Specifications

Diameter (D)	125 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80 mm
Bolt holes Ø	11 mm
Offset (F)	68 mm
Mounting height(H)	195 mm
Load	320 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Plastic
Attributes	
Wheel centre colour	Krémová
Wheel centre	Polyamide
Wheel width (S)	40 mm

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).