Data sheet
734P CFZ-G150



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

Konštručné riešenie of this castors includes fixed rolovaciu vidlicu series 734 with mounting doskou na four otvory, vyrobenú z tvarovo zosilneného steel plechu so zvýšenou pevnosťou and zinc-plated without Cr6, which ensures long-term resistance to corrosion. Thanks to the use of vstrekovaného teplotne durable polyamide wheel centre, which is durable to vysokým temperatures and prasknutiu, is toto castor suitable for applications v pekárňach, where krátkodobo resists temperatures do +300°C, while teplota wheel nesmie prekročiť +250°C. Mechanizmus brake P with dvojpákovým prevedením ON/OFF allows jednoduché zablokovanie rotation wheel for zvýšenú safety. Type bearing - ball, with dvomi radiálnymi guličkovými ložiskami with krytmi, ensures plynulý and non-marking operation, thereby minimises opotrebovanie and reduces potrebu maintenance. An ideal choice for industrial prostredia with vysokými teplotnými nárokmi, where important reliability and durability.

Bracket 734 series:

Fixed castor with plug-in solid stem

- shaped and hardened bearing
- zinc-plated, Cr6-free

Discription of the brake P:

- the brake system prevents the rotation of the wheel double-lever ON/OFF version

Wheel CFZ series:

Injected heat-resistant polyamide:

- highly heat-resistant polyamide
- resistant to cracking
- grey-black color

Application:

- bakeries
- oven temperature short-term up to +300°C
- wheel temperature must not exceed +250 °C

*temperature resistance only applies when using a teflon tube

Bearing - ball:

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).

TREAD AND TYRE HARDNESS	85° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	od -25 °C do +250 °C	

Specifications

Diameter (D)	150 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	200 mm
Load	600 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Plastic
Wheel centre colour	Black
Wheel centre	Polyamide
Typ brzdy	P
Wheel width (S)	50 mm