Data sheet
734P CFZ-G200



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design tejto vidlice series 734 uses tvarovo zosilnený steel plech, which increases strength and durability against deformáciám, while zinc-plated finish without Cr6 ensures long-term protection against corrosion. Wheel series CFZ is made z vstrekovaného teplotne durable polyamidu, which is durable to vysokým temperatures and prasknutiu, with farbou sivo-čierna, which podporuje estetiku and funkčnosť v industrial conditions. Use guličkového bearing with dvoma radiálnymi ložiskami and krytmi ensures plynulý and non-marking operation, znižujúci wear and údržbu. Mechanizmus brake P with dvojpákovým prevedením ON/OFF allows quick and spoľahlivé zablokovanie rotation wheel, thereby increases safety and stability during handling. Thanks to teplotnej odolnosti do 250°C for wheel and krátkodobému use v teplotách do 300°C during použití montážneho kompletu with teflónovým povrchom is toto castor suitable for demanding applications, such as are pekárne alebo iné vysokoteplotné pracoviská, where potrebná reliability and durability.

Bracket 734 series:
Fixed castor with plug-in solid stem

- shaped and hardened bearing
- zinc-plated, Cr6-free

Discription of the brake P:

- the brake system prevents the rotation of the wheel double-lever ON/OFF version

Wheel CFZ series:
Injected heat-resistant polyamide:

- highly heat-resistant polyamide
- resistant to cracking
- grey-black color

Application:

- bakeries
- oven temperature short-term up to +300°C
- wheel temperature must not exceed +250 °C

*temperature resistance only applies when using a teflon tube

Bearing - ball:
When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity = 40%-70%).

TREAD AND TYRE HARDNESS	85° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	od -25 °C do +250 °C	

Specifications

Diameter (D)		200 mm
Plate size (A x B)		135 x 110 mm
Bolt hole spacing (a x b)		105 x 80/75 mm
Bolt holes Ø		11 mm
Mounting height(H)		245 mm
Load		600 kg
Bearing type		Ball
Mounting type		Mounting bracket
Tread material		Plastic
Wheel centre colour		Black
Wheel centre		Polyamide
Typ brzdy		P
Wheel width (S)		50 mm