Data sheet
633X CFZ-G160

Nerezové pevné rolovacie koliesko - spôsob upnutia: montážna doska na štyri otvory (príruba).





VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

INOX
NEHRDZAVEJÚCA OCEĽ

The design of this wheel combines nerezovú montážnu dosku with teplotne durable polyamidovým behúňom, which ensures resistance to prasknutiu and vysokým temperatures až do 250°C during použití with teflónovým povrchom. Use dvoch radiálnych guličkových ložísk with krytmi guarantees plynulý and maintenance-free chod, thereby predlžuje service life and reduces wear. Thanks to tejto odolnosti is wheel suitable for demanding prostredia such as pekárne, where krátkodobá teplota pece can dosiahnuť 300°C, while ensures reliable and bezpečnú operation.

Bracket 633X series:

Fixed castor with top plate (4 bolt holes)

- stainless steel

Wheel CFZ series:

Injected heat-resistant polyamide:

- highly heat-resistant polyamide
- resistant to cracking
- grey-black color

Application:

- bakeries
- oven temperature short-term up to +300°C
- wheel temperature must not exceed +250 °C

*temperature resistance only applies when using a teflon tube

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	85° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -25 °C do +250 °C	

Specifications

Diameter (D)	160 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80 mm
Bolt holes Ø	11 mm
Mounting height(H)	195 mm
Load	320 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Plastic
Attributes	Nehrdzavejúce prevedenie
Wheel centre colour	Black
Wheel centre	Polyamide
Wheel width (S)	40 mm

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).