Data sheet
633X CFZ-G200

Nerezové pevné rolovacie koliesko - spôsob upnutia: montážna doska na štyri otvory (príruba).



VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

INOX
NEHRDZAVEJÚCA OCEĽ

The design of this castor combines vidlicu series 633X z nerezového plechu with mounting doskou na four otvory, which guarantees stable mounting and resistance to corrosion. Wheel centre is made z vstrekovaného teplotne durable polyamidu v sivo-čiernej farbe, which is durable to vysokým temperatures and prasknutiu, while teplota wheel nesmie prekročiť +250°C, which is suitable for krátkodobé vystavenie teplote pece do +300°C. Thanks to the use of dvoch radiálnych guličkových ložísk with krytmi ensures smooth and maintenance-free chod, thereby minimises wear and increases service life. An ideal choice for applications v pekárňach and industrial environments, where potrebná teplotná durability and reliability, while mounting komplet with teflónovým povrchom ešte increases túto durability.

Bracket 633X series:

Fixed castor with top plate (4 bolt holes)

- stainless steel

Wheel CFZ series:

Injected heat-resistant polyamide:

- highly heat-resistant polyamide
- resistant to cracking
- grey-black color

Application:

- bakeries
- oven temperature short-term up to +300°C
- wheel temperature must not exceed +250 °C

*temperature resistance only applies when using a teflon tube

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	85° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -25 °C do +250 °C	

Specifications

Diameter (D)	200 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80 mm
Bolt holes Ø	11 mm
Mounting height(H)	240 mm
Load	350 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Plastic
Attributes	Nehrdzavejúce prevedenie
Wheel centre colour	Black
Wheel centre	Polyamide
Wheel width (S)	50 mm

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).