Data sheet
627P CPS-G200

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model 627 CPS predstavuje konštrukčné riešenie with mounting doskou na four otvory, which ensures stable mounting. Thanks to the use of high-quality bearing (type závisí od konkrétnej varianty) guarantees smooth and non-marking operation with minimálnou údržbou. Tread z thermoplastic elastomer protects podlahové surfaces pred poškodením and redukuje hlučnosť, while the wheel centre and zinc-plated vidlica zvyšujú resistance to corrosion and mechanickému zaťaženiu. Toto castor is suitable for industrial, skladové and komerčné prostredia, where potrebná spoľahlivá brake na zabezpečenie stability nákladu.

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

Diameter (D)		200 mm
Wheel width (S)		50 mm
Plate size (A x B)		135 x 110 mm
Bolt hole spacing (a x b)		105 x 80/75 mm
Bolt holes Ø		11 mm
Offset (F)		60 mm
Mounting height(H)		245 mm
Load		1750 kg
Bearing type		Ball
Mounting type		Mounting bracket
Tread material		Plastic
Attributes		Non-marking
Wheel centre colour		Prírodná biela
Wheel centre		Polyamide
Typ brzdy		P

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).