Data sheet
627P CPS-G250

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model 627 CPS predstavuje konštrukčné riešenie with pozinkovanou vidlicou and termoplastickým elastomérovým behúňom, which minimises noise and wear surfaces. Thanks to the use of high-quality bearing, typicky guličkového, offers hladkú rotáciu and long service life with low údržbou. An ideal choice for industrial and komerčné prostredia, where important reliability and ochrana floor, while brake ensures stability during parkovaní alebo skladovaní.

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

Diameter (D)	250 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	65 mm
Mounting height(H)	295 mm
Load	1750 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Plastic
Attributes	Non-marking
Wheel centre colour	Prírodná biela
Wheel centre	Polyamide
Typ brzdy	P

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).