Data sheet
724 LU-G100-50-50 BR

Swivel castor - mounting type: top plate (4 bolt holes).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)		100 mm
Plate size (A x B)		135 × 110 mm
Bolt hole spacing (a x b)		105 × 80/75 mm
Bolt holes Ø		11 mm
Offset (F)		60 mm
Mounting height(H)		145 mm
Load		350 kg
Bearing type		guličkové
Mounting type		Mounting bracket
Attributes		
Farba behúňa		Hnedá
Wheel centre colour		Hliníková
Wheel centre		Šedá liatina

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).