Data sheet
825 CPD-G100 BR

Swivel castor - mounting type: top plate (4 bolt holes).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	●●●○○

Specifications

Diameter (D)		100 mm
Plate size (A x B)		135 × 110 mm
Bolt hole spacing (a x b)		105 × 80/75 mm
Bolt holes Ø		11 mm
Offset (F)		60 mm
Mounting height(H)		148 mm
Load		700 kg
Bearing type		guličkové
Mounting type		Mounting bracket
Attributes		
Farba behúňa		Prírodná biela
Wheel centre colour		Prírodná biela
Wheel centre		Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).