Data sheet
835 PUC-K200 SS

Fixed castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)	200 mm
Plate size (A x B)	135 × 110 mm
Bolt hole spacing (a x b)	105 × 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	245 mm
Load	600 kg
Bearing type	klzné
Mounting type	Mounting bracket
Attributes	Non-marking
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).