Data sheet
724T ALE-G100 BR

Swivel castor - mounting type: top plate (4 bolt holes).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	65° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	good	●●●○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -30 °C do +80 °C	

Specifications

Diameter (D)		100 mm
Plate size (A x B)		135 × 110 mm
Bolt hole spacing (a x b)		105 × 80/75 mm
Bolt holes Ø		11 mm
Offset (F)		60 mm
Mounting height(H)		145 mm
Load		100 kg
Bearing type		guličkové
Typ brzdy		T
Mounting type		Mounting bracket
Attributes		Ochrana proti poraneniu nôh
Farba behúňa		Čierna
Wheel centre colour		Black
Wheel centre		Hliníková liatina

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).