Data sheet

673 ND-V200 H1

Otočné rolovacie koliesko - spôsob upnutia: upínací driek (hladký čap) - zaisťovací otvor M8 (H1).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	80° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	satisfactory	●●○○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	sufficient	●○○○○
TEMPERATURE RANGE	od -25 °C do +80 °C	

Specifications

Diameter (D)		200 mm
Priemer upínacieho drieku		27 mm
Dĺžka upínacieho drieku		65 mm
Offset (F)		56 mm
Mounting height(H)		235 mm
Load		205 kg
Bearing type		ihlové
Mounting type		Hladký driek
Farba behúňa		Čierna
Wheel centre colour		Black
Wheel centre		Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).