Data sheet
836 CL-G250

Fixed castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

Thanks to the use of thermoplastic elastomer v behúni and high-quality bearing, toto fixed rolovacie castor provides maintenance-free operation with low hlučnosťou. An ideal choice for applications v industrial alebo komerčných priestoroch, where important reliability and protection of floor surfaces. Zinc-plated vidlica and robustná konštrukcia zaisťujú long service life aj during intenzívnej záťaži.

TREAD AND TYRE HARDNESS	180 – 220 HB	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	sufficient	●○○○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	from -100 °C to +600 °C (bearing K)	
TEMPERATURE RANGE	from -20 °C to +120 °C (bearing G)	

Specifications

Diameter (D)	250 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	297 mm
Load	1000 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Kov
Attributes	
Wheel centre colour	Black
Wheel centre	Šedá liatina
Wheel width (S)	54 mm

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).