Data sheet
623 ALUO-G125

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

Vidlica series 623 is made z steel plechu with pozinkovaním without Cr6, which ensures antikoróznu protection and long service life. Wheel centre z hliníkovej zliatiny is vystužený rebrovaním, which increases jeho durability. Tread z liateho polyurethane elastoméra is chemicky combined with wheel centre, which ensures high únosnosť and elasticity. Dvojité axial ball bearing with kalibrovanými dráhami guarantees plynulý and non-marking operation. An ideal choice for tvrdé aj mäkké industrial floor, suitable for stredné nerovnosti and nepretržitú operation.

TREAD AND TYRE HARDNESS	87° ± 5° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Bracket 623 series:

Swivel castor with top plate (4 bolt holes)

- standard version
- pressed steel, THK 3 ÷ 4 mm
- double bearing with calibrated races
- seal in the swivel head
- zinc-plated, Cr6-free

Wheel ALUO series:

Wheel center:

- die-cast aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

Tread:

- casted polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- High-profile rounded shape
- good elasticity, good at preserving floor surfaces
- non-marking
- low level of starting and rolling resistance
- cream color RAL 9001

Application:

- hard and soft industrial floor surfaces
- mild obstacles
- continuous operation

Specifications

Diameter (D)	125 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	165 mm
Load	350 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Krémová
Wheel centre colour	Hliníková
Wheel centre	Hliníková liatina

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).