Data sheet
638 XJ-G260

Fixed castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this pevného rolovacieho castors combines steel plechový wheel centre with nafukovacím behúňom, which allows tlmenie noise and gentleness k podlahe. Vidlica series 638 is made z pozinkovaného steel plechu without Cr6, which increases durability against corrosion. Model uses dve radiálne ball bearings with krytmi, which ensure plynulú and maintenance-free operation. An ideal choice for easy manipulačnú techniku with nosnosťou do 150 kg, suitable for prostredia with malou frekvenciou use, such as are rudlíky, where important quiet and reliable chod.

Bracket 638 series:

Fixed castor with top plate (4 bolt holes)

- pressed steel
- zinc-plated, Cr6-free

Wheel XJ series:

Rim:

- pressed steel

Tyre:

- pneumatic tyre and inner tube
- grooved or smooth tread
- good floor preservation properties
- low-noise operation
- black color

Application:

- light duty handling equipment to 150 kg
- suitable for short distances
- hand trucks

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	60° Shore A	●○○○○
ROLLING RESISTANCE	good	●●●○○
OPERATING NOISE	excellent	●●●●●
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	od -20 °C do +50 °C	

Specifications

Diameter (D)	260 mm
Wheel width (S)	85 mm
Plate size (A x B)	195x160 mm
Bolt hole spacing (a x b)	160x120 mm
Bolt holes Ø	14,5 mm
Mounting height(H)	308 mm
Load	130 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Pneumatika
Farba behúňa	Čierna
Wheel centre colour	Black
Wheel centre	Oceľ

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).