Data sheet
373F NOB-K075

Swivel castor - mounting type: plug-in solid stem, with brake.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this castor includes zinc-plated vidlicu with upínacím driekom for easy installation na steel plech. Thanks to dvojradovému axial bearing ensures plynulú swivel operation, while the mechanizmus brake F allows zablokovanie v akomkoľvek direction. Wheel centre z durable polypropylene is mechanicky combined with tmavo-sivým behúňom, which guarantees a long service life and resistance to prasknutiu. Klzné bearing v wheel centre provides maintenance-free operation, odolnú to dirt and external vplyvom, vhodnú for short transport distances v various environments.

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Bracket 373 series:
Swivel castor with plug-in solid stem

- pressed steel, THK 2,5 mm
- double-row axial bearing in the swivel head
- zinc-plated, Cr6-free

Discription of the brake F:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel NOB series:
Wheel center:

- polypropylene
- impact resistant
- light-grey color

Tread:

- thermoplastic rubber elastomer
- chemically-bonded inseparable connection with the wheel center
- silent operation
- non-marking
- dark-grey color

Application:

- light-duty handling equipment
- suitable for warehouses, small productions and operations

Specifications

Diameter (D)	75 mm
Wheel width (S)	30 mm
Priemer upínacieho drieku	20 mm
Dĺžka upínacieho drieku	45 mm
Offset (F)	32 mm
Mounting height(H)	100 mm
Load	80 kg
Bearing type	Klzné
Mounting type	Hladký driek
Tread material	Guma a TPE
Attributes	Non-marking
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polypropylén
Typ brzdy	F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).