Data sheet
323F NOB-K075

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this rolovacieho castors z radu 323F NOB-K uses montážnu dosku na four otvory (príruba), which allows stable and bezpečné mounting. Thanks to the use of high-quality material tread and durable wheel centre achieves produkt high load capacity and long service life. Technické parametre zahŕňajú efektívny brzdový systém for secure fixation polohy and suitable bearing, which ensures plynulý and quiet operation. An ideal choice for industrial and komerčné prostredia, where potrebná spoľahlivá manipulácia with nákladom and protection of floor surfaces.

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)	75 mm
Wheel width (S)	30 mm
Plate size (A x B)	95 x 70 mm
Bolt hole spacing (a x b)	75/72 x 52/45 mm
Bolt holes Ø	9 mm
Offset (F)	32 mm
Mounting height(H)	100 mm
Load	80 kg
Bearing type	Klzné
Typ brzdy	F
Mounting type	Mounting bracket
Tread material	Guma a TPE
Attributes	Non-marking
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).