Data sheet
423 PYR-V100

Swivel castor - mounting type: top plate (4 bolt holes).

The design of this rolovacieho castors uses montážnu dosku na four otvory (príruba) for simple and bezpečnú installation. Zinc-plated vidlica increases durability against corrosion, while the thermoplastic elastomérový tread provides excellent trakciu and tlmenie vibrácií, thereby minimises noise and wear floor. Klzné bearing ensures plynulý and maintenance-free chod, suitable for stredne zaťažené prostredia such as sklady, dielne alebo kancelárske priestory. An ideal choice for vyhľadávač produktov v sérii 423 PYR, where reliability and efektivita are kľúčové.

TREAD AND TYRE HARDNESS	75° ± 2° Shore A
ROLLING RESISTANCE	good
OPERATING NOISE	very good
WEAR RESISTANCE	good
TEMPERATURE RANGE	od -30 °C do +70 °C

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).