Data sheet
473 PYR-V125

The design of this wheel spočíva v spojení pevného polypropylene wheel centre with elastickým rubber tread, which absorbuje vibrations and reduces hlučnosť. Klzné bearing ensures plynulý and bezstopý movement without potreby mazania, thereby minimises údržbu. Zinc-plated vidlica increases resistance to corrosion, which ho robí vhodným for various pracovné prostredia. An ideal choice for applications vyžadujúce reliable and quiet movement nákladu.

TREAD AND TYRE HARDNESS	75° ± 2° Shore A	●●●○○
ROLLING RESISTANCE	good	●●●○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity = 40%-70%).