Data sheet
NL-V125/15S c/d

Wheel.

The series model NL predstavuje konštrukčné riešenie with pozinkovanou vidlicou and polypropylene wheel centre, which is durable to corrosion and chemicals. Tread z thermoplastic elastomer guarantees quiet and gentle movement po floors, while plain bearing minimises friction and allows long-term operation without nutnosti maintenance. An ideal choice for use v industrial, komerčných aj domácich priestoroch, where important reliability and gentleness k povrchom.

TREAD AND TYRE HARDNESS	90° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	satisfactory	●●○○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	sufficient	●○○○○
TEMPERATURE RANGE	od -25 °C do +80 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).