Data sheet
XD-V200/20

Wheel.



The series model XD uses konštrukčné riešenie with oceľovým pozinkovaným wheel centre without Cr6 and štandardným plným rubber tread, which ensures non-marking operation and gentleness k jazdnému surface. Thanks to the use of ihlového bearing, where vonkajší krúžok tvorí material wheel centre with tvrdosťou 25 HRC and klietkou z polyamidu PA6, achieves reliable operation with low údržbou. An ideal choice for sklady, malé výroby and operation, where vyžaduje tichá manipulácia na short transport distances.

Wheel XD series:

Rim:

- pressed steel
- zinc-plated, Cr6-free

Tyre:

- premium solid rubber
- high operational comfort
- good floor preservation properties
- low-noise operation
- black color

Application:

- light-duty handling equipment
- suitable for warehouses, small productions and operations

Bearing - roller:

- the outer ring of the bearing formed by the wheel center material
- steel needles, hardness 25 HRC
- polyamide cage PA6
- suitable for short distances

Specifications

Diameter (D)	200 mm
Wheel width (S)	46 mm
Load	150 kg
Vnútorný priemer náboja (d)	20 mm
Dĺžka náboja (L)	55 mm
Bearing type	Ihlové
Tread material	Guma a TPE
Farba behúňa	Čierna
Wheel centre colour	Black
Wheel centre	Oceľ

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).