Data sheet
LUZ-082-70

Wheel.



The series model LUZ is designed with jednodielnym wheel centre zo šedej liatiny (STN 42 2420), which is zosilnený load-bearing rebrom and chránený antikoróznym náterom. Tread z liatého polyurethane elastomer is non-detachably chemicky combined with wheel centre, which guarantees high húževnatosť and wear resistance. Thanks to the use of polyuretánu wheel nepoškodzuje and nefarbí floor, while provides nízky rozbehový and valivý odpor. The design is primárne určené for nízkozdvižné and vysokozdvižné ručné trolleys v environments with rovnými polyuretánovými podlahami, where ensures non-marking operation and long service life.

Wheel LUZ series:

Wheel center:

- one-piece
- grey cast iron (STN 42 2420)
- reinforced supporting rib
- anti-corrosion paint
- grey color

Tread:

- casted polyurethane elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity and good at preserving floor surfaces
- non-marking
- low level of starting and rolling resistance
- brown color

Application:

- even polyurethane floors
- primarily intended for pallet trucks and forklift trucks

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)		82 mm
Wheel width (S)		70 mm
Mounting height(H)		82 mm
Load		700 kg
Vnútorný priemer náboja (d)		47 mm
Dĺžka náboja (L)		70 mm
Bearing type		-
Tread material		Polyuretán
Farba behúňa		Hnedá
Wheel centre colour		Sivá
Wheel centre		Šedá liatina

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).