Data sheet
LU-G150-40-50/25

Wheel.



The series model LU is konštrukčne designed with jednodielnym liatinovým wheel centre v šedej farbe, which is zosilnený load-bearing rebrom and chránený antikoróznym náterom for long service life. Tread z liateho polyurethane elastomer is chemicky combined with wheel centre, which guarantees excellent elasticity and schopnosť absorbovať high load, while nepoškodzuje ani nefarbí floor. Use dvoch radiálnych guličkových ložísk with krytmi reduces rozbehový and valivý odpor, supporting non-marking operation and maintenance-free operation. Toto wheel is optimálne for straight betónové floor with miernymi nerovnosťami, vďaka čomu is suitable do demanding industrial prostredí with nepretržitou prevádzkou.

Wheel LU series:

Wheel center:

- one-piece
- grey cast iron (STN 42 2420)
- reinforced supporting rib
- anti-corrosion paint
- grey color

Tread:

- casted polyurethane elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity and good at preserving floor surfaces
- non-marking
- low level of starting and rolling resistance
- brown color

Application:

- flat concrete floors
- small obstacles
- continuous operation

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)		150 mm
Wheel width (S)		40 mm
Load		550 kg
Vnútorný priemer náboja (d)		25 mm
Dĺžka náboja (L)		50 mm
Uloženie ložísk (L1)		46 mm
Bearing type		Ball
Attributes		Non-marking
Farba behúňa		Hnedá
Wheel centre colour		Sivá
Wheel centre		Šedá liatina

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).