Data sheet
LK-G145/8S POLYUR

Wheel.



The series model LK-G is konštruovaný with polyurethane tread, which provides high durability against wear and quiet operation, ideálny for interiérové applications. Wheel centre z thermoplastic elastomer ensures flexibilitu and resistance to nárazom, while plain bearing allows smooth movement without the need for maintenance. This wheel is suitable for use v kancelárskych, industrial alebo logistics environments, where important gentleness k podlahe and reliability. The design with pozinkovanou vidlicou increases resistance to corrosion, thereby predlžuje service life produktu.

Specifications

Diameter (D)	145 mm
Wheel width (S)	30 mm
Bearing type	Ball
Vnútorný priemer náboja (d)	8 mm
Dĺžka náboja (L)	35 mm
Load	70 kg
Obruč	Guma a TPE
Farba obruče	Sivá
Wheel centre	Polyamide
Wheel centre colour	Black
Attributes	Non-marking

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).