Data sheet
Shopping cart 80L







The design of this nákupného vozíka vychádza z kombinácie durable polypropylene wheel centre with rubber tread, which guarantees bezstopý and quiet movement. Thanks to the use of klzného bearing achieves maintenance-free operation and long service life. Zinc-plated vidlica increases resistance to corrosion, which is výhodou v environments with vyššou vlhkosťou. An ideal choice for obchodné reťazce, sklady and výrobné haly, where important smooth and reliable transport nákladu.

Specifications

Nosnosť-horný kôš	30 kg
Nosnosť-spodná plošina	100 kg
Kolesá-polyp.+termopl. guma	351 NOB-g125p mm
Rozmery plošiny	480x740 mm
Rozmery košíka	330x530 mm
Celkové rozmery	600x970 mm
Výška rukoväte	1120 mm
Hmotnosť	25 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).