# Data sheet
# Universal storage truck-2 UNI /500X290/40



The design of this skladového vozíka series SV-2 UNI spočíva v spojení durable wheel centre with rubber tread z thermoplastic elastomer, which guarantees quiet and non-marking operation. Thanks to the use of klzného bearing is vozík ideálny for intenzívnu operation v skladoch and production priestoroch, where vyžaduje minimálnu údržbu. Zinc-plated vidlica increases durability against corrosion, which robí tento model vhodným for various pracovné prostredia. An ideal choice for manipuláciu with nákladom do 400 kg with rozmerom plošiny 500x290 mm.

## Specifications

| | |
|---|---|
| Load | 400 kg |
| Výška x šírka | 1140x680 mm |
| Plošina - šírka x hĺbka | 500x290 mm |
| Rozmer kolies | nafukovacie Ø 300 mm |
| Hmotnosť | 16,5 kg |

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).