Data sheet
Universal storage truck-2 UNI /500X290/ 35



The design of this skladového vozíka uses zinc-plated vidlicu, which ensures high durability against corrosion and long service life. Thanks to the use of rubber tread with termoplastickým elastomérom achieves non-marking operation, thereby minimises noise and protects floor surfaces. Klzné bearing ensures maintenance-free operation, while the robustná konštrukcia with nosnosťou 350 kg allows spoľahlivé use v demanding conditions, such as are sklady alebo výrobné haly. Tento model is optimalizovaný for univerzálne use, ponúkajúc stability and easy ovládateľnosť during handling with nákladom.

Specifications

Load	350 kg
Výška x šírka	1117x650 mm
Plošina - šírka x hĺbka	500x290 mm
Rozmer kolies	nafukovacie Ø 300 mm
Hmotnosť	16 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).