Data sheet
Universal storage truck-2 UNI /300X220/25



The series model SV-2 offers konštrukčné riešenie with pozinkovanou vidlicou, which increases durability against corrosion, and polypropylene wheel centre spojeným with modrým rubber tread for plynulý and quiet movement. Thanks to the use of klzného bearing ensures maintenance-free operation and long service life, while tread z thermoplastic elastomer minimises wear floors. Tento vozík is optimalizovaný for univerzálne use v demanding environments, supporting efektívnu manipuláciu with rozmermi 300x220 mm and maximálnou záťažou 250 kg.

Specifications

Load	200 kg
Výška x šírka	1100x570 mm
Plošina - šírka x hĺbka	400x170 mm
Rozmer kolies	nafukovacie Ø 260 mm
Hmotnosť	9,1 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).